

VS1601

16-Port Video Switch


- The VS1601 Video Switch is a control unit that allows you to conveniently display the video output of sixteen separate computer systems on a single monitor, or via a multimedia projector. It features stereo audio support; easy computer selection via pushbuttons; intelligent infrared (IR) remote control.

The VS1601 is rack mountable and occupies 1U of space; furthermore, it saves extra monitor space, extra power costs, and eliminates the inconvenience and wasted effort involved in constantly moving around from one computer to another.



Features

- Displays the video output of sixteen computers on a single monitor or projector
 - Quick and easy switching via front panel pushbuttons or IR remote control
 - External IR receiver (1.8 m) for maximum efficiency and convenience
 - Audio-enabled
 - Supports up to 250 MHz bandwidth
 - Long-distance transmission – up to 65 m
 - Superior video quality – up to 1920 x 1440 @ 60Hz; DDC; DDC2; DDC2B
 - Supports VGA, SVGA, XGA, SXGA, UXGA, WUXGA and multisync monitors
 - Designed for enterprise use – 1U in size and rack mountable
- * Video content sent over very long distance using a VGA cable might result in slight degradation of the video signal and quality.



Specification

Function	VS1601	
Computer Connections	16	
Port Selection	Pushbutton; IR Remote Control	
Connectors	Video In	16 x HDB-15 Male (Blue)
	Audio In	16 x Mini Stereo Jack Female (Green)
	Video Out	1 x HDB-15 Female (Blue)
	Audio Out	1 x Mini Stereo Jack Female (Green)
	IR	1 x Mini Stereo Jack Female (Black)
	Power	1 x DC Jack
LEDs	On Line / Selected	16 (Orange/Green)
	Video Out Display On/Off	1 (Blue)
Switches	Power	1 x Rocker
	Port Up	1 x Pushbutton
	Port Down	1 x Pushbutton
Video	1920 x 1440 @ 60Hz (max); DDC2B	
Signal Range	65 m	
Power Consumption	DC5V, 2.5W	
Environment	Operating Temp.	0 – 50°C
	Storage Temp.	-20 – 60°C
	Humidity	0 – 80% RH, Non-condensing
Physical Properties	Housing	Metal
	Weight	2.60kg
	Dimensions (L x W x H)	43.72 x 16.32 x 4.40 cm

* Product specifications and appearance are subject to change without notice.

